



BioD-Watl™ 6

Lightly packed coir wattles for sediment control

Completely Wildlife Safe!

Description

This is to certify that the BioD-Watl™ 6 coir wattles are 6 in (15 cm) diameter cylindrical shape rolls. The 2 in x 2 in (5 cm x 5 cm) knotted, high strength outer netting is made of 60 lbs (267 N) strength machine spun bristle coir twines. They are lightly packed with cleaned mattress coir fiber in a uniform manner to filter sediment effectively. The BioD-Watl 6 is made to 15 ft long sections. BioD-Watl™ 6 coir wattles are manufactured to conform to the following properties:

Specifications

Property	BioD-Watl™ 6
Unit Weight	0.6 lb /ft (1 kg/m)
Density	3.4 lb /cu ft. (55 kg /cu. m.)
Filler material	100% coconut fiber (mattress coir fiber)
Size	
Length	15 ft. (4.6 m)
Diameter	6 in (15 cm)
Outer netting	Bristle coir twine
Mesh opening	2 in X 2 in (5 cm x 5 cm)
Tensile strength / twine	60 lbs. (267 N)



155 Andrew Drive, Stockbridge, GA 30281

1 800 760 3215

Tel: 770 506 8211 Fax: 770 506 0391

E-mail: rolanka@rolanka.com

Web: www.rolanka.com

SBA's 8(a) & SDB and DOT DBE Certified